

Mipro Products

PORTABLE PA Systems

MA-808 Wireless Portable PA System

Features

- Huge 250-watt power and 123dB SPL for crowds up to 2,000.
- Class-D and Class-AB amplifiers drive 2-way speakers.
- Robust design with retractable handle and sturdy wheels for easy transport.
- Up to 4 diversity UHF 16 scanable frequency receivers.
- Press "SCAN" button receiver automatically scans for an open, interference-free frequency.
- Press "ACT" button syncs the receiver and transmitter frequencies automatically.
- 3 power modes: AC, rechargeable battery and direct DC.
- Industry's only MTM-90 wireless interlinking transmitter option to interlink multiple.
- MIPRO MA-808 portables wirelessly to extend transmission range and expand coverage.
- External speaker output powers a passive extension speaker.
- XLR & 1/4" combo jack for one wired dynamic microphone.
- Line-in for audio playing / Line-out for external recording.
- Active limiter – keeps sounds clean when driven hard.
- A voice priority feature that mutes the music when mic is used.
- A smart 4-segment battery meter for accurate battery reading and charging status.
- Echo effect control so singers sound fuller and richer.
- Built-in storage compartments for 2 transmitters.
- 5~6 hours continuous use per charge.
- 90~264V auto-switching AC power supply.



Specifications

Power Output	250-Watt, HF 8Ω / LF 4Ω
T.H.D.	<0.1%
Frequency Response	50Hz~18KHz
Treble Speaker	1.5-inch, Titanium Compression Driver
Bass Speaker	10-inch, Neodymium Cone Driver
Active Crossover Filter	2.5kHz / -12dB oct
Operating Mode	Direct operation on speaker unit
3 in 1 Recorder / Player	Plays music CD or SD card.
Audio Inputs	Balanced, Unbalanced Mic & Line-in
Power Supply	Built-in two pieces of 12V/4.5AH rechargeable battery with charger & 90~264V AC switching power supply.
Charging & Operating Time	6~8 hours charge for 5~6 hours use. (automatic charging management)
Dimensions	360(W)×560(H)×350(D)mm / 14.2(W)×22.0(H)×13.8(D)"
Weight	20.5kg / 45.2lbs
Exterior Color	Black
Matching Transmitters	ACT-707HE , ACT-707TE
Matching cabled microphone	MM-107
Note	Varied specifications on carrier frequency range, maximum deviation, RF output power and spurious emission to comply regulation of different countries.

Matching Microphones



ACT 707HE

ACT 707TE

MM107